

FILTER SAND

SPECIALTY

SAND PRODUCTS

MANUFACTURER:

Ace-Crete/New Jersey Pulverizing
 4 Rita Street • Syosset, NY 11791
 (516) 921-9595 • Fax (516) 921-9575

PRODUCT DESCRIPTION:

Our high purity, high silica, sands is a natural product of the Ice Age. The sand is subangular and comes in many grades, meeting different specification standards and AWWA designations and standards.

USE:

Rapid sand filters

Coverage:

50 pounds of sand is approximately ½ cubic foot, 6' x 6' x 6'.

Packaging:

Available in 50 pound multi-wall paper bags.


Color:

Our filter sand is a light yellowish-tan color.

TECHNICAL DATA:

Filter sand will be in the .65 to .95 mm range and will meet various AWWA standards, including B-100-89

Moh Hardness6 to 8
 Specific Gravity2.54 to 2.71
 Acid Solubility0.08 to 0.11
 Standard uniformity
 Coefficient less than 1.5



Typical Chemical Analysis:

SiO ₂	98.93	CaO	0.02
Fe ₂ O ₃	0.54	MgO	0.01
Al ₂ O ₃	0.41	Sulfate	
.	trace		
TiO ₂	0.09	L.O.I.	0.11

CAUTION:

Sand CAS # 14808-60-7. Avoid breathing dust. Prolonged exposure to dust may cause Silicosis or Scleroderma. Crystalline Silica has been classified by IARC and NPT as a carcinogen. Wear NOSH approved mask for silica dust. **Keep Out Of Reach Of Children.**

WARRANTY:

Due to the use of this product beyond our control, we assume no liability for damages of any kind, and the user accepts the product "as is" and without warranties, expressed or implied, from either Ace-Crete/New Jersey Pulverizing Products or its agents. The suitability of the product for an intended use shall be solely up to the user. Our only obligation shall be to replace or pay for any material proved defective, with our liability limited to the purchase price of materials supplied by us.

