

MATERIAL SAFETY DATA SHEET

Date: July 1, 2004

SECTION I - GENERAL INFORMATION

MANUFACTURER'S NAME: Ace-Crete Products, Inc.
MANUFACTURER'S ADDRESS: 4 Rita Street
Syosset, New York 11791
EMERGENCY PHONE NUMBER: (516) 921-9595

PRODUCT NAME: BLACK TOP, ASPHALT PAVER
TRADE NAME AND SYNONYMS: Ace-Crete Black Top Patch
CHEMICAL NAME: Asphalt
CHEMICAL FAMILY: Asphalt Bitumen/MC-250 Liquid Sand
FORMULA:

SECTION II - HAZARDOUS INGREDIENTS

<u>COMPONENT</u>	<u>CAS #</u>	<u>%</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>
Asphalt MC-250		8%		
Inert Filler		92%		

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

333
BOILING POINT: N/A
MELTING POINT: N/A
VAPOR PRESSURE (mm Hg.): N/A
VAPOR DENSITY (AIR = 1): N/A
SOLUBILITY IN WATER: 0.0
SPECIFIC GRAVITY (H₂O = 1): 2.26
PERCENT VOLATILE BY VOLUME: 2.1%
EVAPORATION RATE (___ = 1): N/A
APPEARANCE AND ODOR: Black Aggregate Patch

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (METHOD USED): Tag. Closed Cup 150°
FLAMMABLE LIMITS: 550°+ **LEL:** 0.9% **UEL:** 6.0%
EXTINGUISHING MEDIA: Water, Dry Chemical, Foam, Carbon Dioxide
SPECIAL FIRE FIGHTING PROCEDURES: Avoid breathing vapor or fumes
UNUSUAL FIRE AND EXPLOSION HAZARDS: Water and foam may cause frothing

SECTION V - REACTIVITY DATA

STABILITY: **UNSTABLE:** ___ **STABLE:** X
CONDITIONS TO AVOID: Open flame - Excessive heat

INCOMPATIBILITY (MATERIALS TO AVOID): N/A
HAZARDOUS DECOMPOSITION PRODUCTS: N/A

HAZARDOUS POLYMERIZATION: **MAY OCCUR:** ___ **WILL NOT OCCUR:** X
CONDITIONS TO AVOID: None

Black Top Patch

