

PATCH IT

Fast Setting Polymer Modified
Repair Mortar

PATCHING AND REPAIR FAST SETTING

MANUFACTURER:

Empire Blended Products, Inc.
250 Hickory Lane • Bayville, NJ 08721
(732) 269-4949 • Fax (732) 269-0497

PRODUCT DESCRIPTION:

PATCH IT is a fast setting, single component repair mortar for use over concrete, masonry and wood. Portland Cement based and polymer modified, it provides a high bonding and high strength patch from ½" down to a featheredge. Its accelerated set time (20 minutes) allows for quick finishing and short down time.

USES:


- Patch spalled concrete areas
- Level low areas in concrete slabs
- Setting bed for brick, flagstone, quarry tile, pavers, etc.
- Repoint all masonry joints and grouting between floor tile, marble and flagstone
- Concrete floors, driveways, walkways, steps and patios
- Horizontal or vertical surfaces
- Indoors or outdoors, above or below grade

ADVANTAGES:

- Fast setting - 20 minutes
- One component, add water only
- Easy to apply
- High bond and compressive strength
- Self-curing, natural cement color
- Can be featheredged
- Non-shrink, non-staining
- Accepts cement based and latex paints after curing
- Provides water resistant finish

Placement:

Place mixed material with a steel trowel, applying



INSTALLATION:

Surface Preparation:

Surfaces to be coated must be structurally sound, clean, and free of dust, dirt, oils, paints and all other contaminants that will prevent proper bond. RAINBOW PURE TRI SODIUM PHOSPHATE is an excellent heavy duty cleaner to use. Loose concrete and rust on steel rods must be removed by sandblasting, waterblasting, chipping or wire brushing. Coat all metal with a slurry coat of *PATCH IT* and EMPIRE BLENDED EM-CRYL 600. Floors that have been polished smooth or sealed should be tested for adhesion. To test, apply a sample patch at least 1 square foot, wait 2-4 days, and then try to lift the patch with a screwdriver. All mortar joints to be repointed must be free of any loose mortar and cut back to a sound surface. Flush all joints clean with water or compressed air. Dampen surface with clean water to the point of saturation but allow no standing water prior to placing material.

Mixing:

Add clean water to a suitable, clean container at the rate of 1 quart for each 15 pounds of *PATCH IT*. Mix to a creamy lump-free mortar consistency suitable for the application. Excessive amounts of water will decrease the strength of the patch. Do not mix more material than can be placed in 15 minutes.

pressure to ensure complete filling of all voided areas, but do not overtrowel. Finish with steel

trowel, brush or sponge. Keep trowel wet when finishing to avoid pulling material and clean immediately after use with clean water. For areas deeper than ½" place material in successive layers, scoring previous layer with trowel after placing. Allow first layer to harden before placing next layer. For areas greater than ½" thick which must be repaired in 1 layer, use EMPIRE BLENDED PATCH ALL. When repointing masonry joints, dampen joints slightly, then apply *PATCH IT* by using a tuck pointing trowel forcing the material into all voided areas. For joints deeper and or wider than ½", backfill first to within ¼" of finish surface and allow backfilled area to cure 24 hours before finish coat is applied.

Curing:

PATCH IT is self-curing under most conditions, however like all cement based products, moist curing is preferable. Repaired areas exposed to high temperatures, direct sunlight or extremely windy conditions should be lightly misted with water or covered with damp burlap for 24 hours. Most applications under normal conditions can be used for light traffic after 2 hours.

Coverage:

1 pound of *PATCH IT* covers approximately 1 square foot at ½" thickness. Used as a repointing mortar, 1 pound will fill 17 cubic inches.

Packaging:

Available in 40 pound multiwall paper bags with moisture barrier.

Color:

Light Gray

TECHNICAL DATA:

TEST	7 DAY PSI	28 DAY PSI
Compressive	4,250	5,450
Tensile	385	475
Flexural	700	825
Shear Bond	390	490

LIMITATIONS:

Do not use when temperature is below 40°F or expected to fall below 40°F within 24 hours of application. Do not use any additives.

CAUTION:

Contains Portland Cement CAS #65997-15-1. Freshly mixed cement products may cause skin injury. Avoid contact with skin where possible and wash exposed areas promptly with water. If any product gets into the eye, rinse immediately and repeatedly with water. If ingested, **do not** induce vomiting and get prompt medical attention. Also contains Sand CAS #14808-60-7. Avoid breathing dust. Prolonged exposure to dust may cause delayed lung injury (silicosis) or cancer IARC Class 2A. Wear NIOSH approved mask for silica dust. **Keep Out Of Reach Of Children.**

WARRANTY:

Due to the use of this product beyond our control, we assume no liability for damages of any kind, and the user accepts the product "as is" and without warranties, expressed or implied, from either Empire Blended Products or its agents. The suitability of the product for an intended use shall be solely up to the user. Our only obligation shall be to replace or pay for any material proved defective, with our liability limited to the purchase price of materials supplied by us.